


intra




HOSES

AGROFLAT | MONOFLAT | SPIRAL HOSES | GARDEN HOSES




AGROFLAT SL	Model	Inside Dia	Weight	Pressure		Price
	Code	mm	Kg/m	Working	Rupture	€ / m
				bar	bar	
	210390-040	40	0,240	5,0	12,5	
	210390-050	50	0,300	5,0	12,5	
	210390-063	63	0,410	4,5	11,3	
	210390-070	70	0,430	4,5	11,3	
	210390-075	75	0,450	4,0	10,0	
	210390-090	90	0,590	4,0	10,0	
	210390-100	100	0,690	3,0	7,5	
	210390-110	110	0,720	3,0	7,5	
	210390-125	125	0,880	3,0	7,5	
	210390-150	150	1,050	3,0	7,5	


FEATURES: Flat hose reinforced with polyester yarn; very light. Working pressure determined at 20°C, before perforation of hoses. APPLICATIONS: Mainly for drip irrigation and conveying water at low pressure. TEMPERATURE RANGE: -10/+55°C | PRESENTATION: Color: yellow.

AGROFLAT	Model	Inside Dia	Weight	Pressure		Price
	Code	mm	Kg/m	Working	Rupture	€ / m
				bar	bar	
	210391-025	25	0,185	9,0	22,5	
	210391-032	32	0,210	9,0	22,5	
	210391-035	35	0,230	8,0	20,0	
	210391-038	38	0,240	7,0	17,5	
	210391-040	40	0,260	7,0	17,5	
	210391-045	45	0,290	7,0	17,5	
	210391-050	50	0,330	6,5	16,3	
	210391-055	55	0,360	6,5	16,3	
	210391-063	63	0,410	6,5	16,3	
	210391-070	70	0,530	6,0	15,0	
	210391-075	75	0,550	5,0	12,5	
	210391-080	80	0,580	5,0	12,5	
	210391-090	90	0,660	5,0	12,5	
	210391-100	100	0,760	4,0	10,0	
	210391-125	125	1,100	4,0	10,0	
	210391-150	150	1,250	3,5	8,5	


FEATURES: Flexible flat hose, reinforced with polyester yarn, very light and resistant. APPLICATIONS: Mainly for conveying water at low pressure and drip irrigation. TEMPERATURE RANGE: -10/+55°C | PRESENTATION: Color: green.

AGROFLAT M	Model	Inside Dia	Weight	Pressure		Price
	Code	mm	Kg/m	Working	Rupture	€ / m
				bar	bar	
	210393-025	25	0,250	10,00	31,50	
	210393-032	32	0,300	10,00	31,50	
	210393-038	38	0,330	10,00	31,50	
	210393-040	40	0,340	10,00	31,50	
	210393-045	45	0,430	10,00	31,50	
	210393-050	50	0,480	8,50	26,80	
	210393-055	55	0,490	8,50	26,80	
	210393-063	63	0,585	8,50	26,80	
	210393-067	67	0,660	7,00	22,00	
	210393-070	70	0,680	7,00	22,00	
	210393-075	75	0,770	7,00	22,00	
	210393-090	90	0,880		22,00	
	210393-100	100	0,980	6,00	19,00	
	210393-125	125	1,300	5,00	16,00	
	210393-150	150	1,600	5,00	16,00	
	210393-200	200	2,400	2,50	7,80	


FEATURES: Flat hose reinforced with polyester yarn, very resistant, for medium pressure. APPLICATIONS: Mainly for conveying water. TEMPERATURE RANGE: -10/+55°C | PRESENTATION: Color: blue.

AGROFLAT H	Model	Inside Dia	Weight	Pressure		Price
	Code	mm	Kg/m	Working	Rupture	€ / m
				bar	bar	
	210394-025	25	0,250	15,0	48,80	
	210394-045	45	0,500	13,5	42,50	
	210394-050	50	0,600	12,0	37,80	
	210394-063	63	0,760	12,0	37,80	
	210394-070	70	0,840	11,5	36,20	
	210394-075	75	0,880	11,5	36,20	
	210394-090	90	0,980		36,20	
	210394-100	100	1,300	10,0	31,50	
	210394-150	150	2,000	7,0	22,00	
	210394-200	200	3,300	5,0	15,50	

FEATURES: Flat hose, reinforced with polyester yarn, very resistant, for high pressure. APPLICATIONS: Mainly for conveying water. Can also be used with sprinkler irrigation equipment, particularly rain guns. TEMPERATURE RANGE: -10/+55°C | PRESENTATION: Color: inside and outside black.

MONOFLAT	Model	Inside Dia	Weight	Pressure		Price
	Code	mm	Kg/m	Working	Rupture	€ / m
				bar	bar	
	210381-038	38	0,220	7,0	17,50	
	210381-053	53	0,290	6,5	16,30	
	210381-070	70	0,435	5,5	13,80	
	210381-078	78	0,460	5,0	12,50	

FEATURES: Flat hose reinforced with polyester yarn; very light. Working pressure determined at 20°C, before perforation of hoses. APPLICATIONS: Mainly for drip irrigation and conveying water at low pressure. TEMPERATURE RANGE: -10/+55°C

MONOFLAT	Model	Inside Dia	Weight	Pressure		Price
	Code	mm	Kg/m	Working	Rupture	€ / m
				bar	bar	
	210381-090	90	0,590			
	210381-103	103	0,650			
	210381-128	128	0,880			
	210381-155	155	1,150			

PRESENTATION Color: blue. | Available in lengths of 25, 50 and 100 meters, depending on the diameters. | Packaging: PE film and strap or box only when the flat hose is supplied with fittings | Note: other colors, diameters and lengths available upon request.



HELIFLEX SL



Model	Inside Dia	Weight	Bend Radius	Thick	Price
Code	mm	Kg/m	mm	mm	€ / m
230011-020	20	0,230	100	2,6	
230011-025	25	0,270	125	2,7	
230011-030	30	0,340	150	2,8	
230011-032	32	0,335	160	3,2	
230011-035	35	0,425	160	3,1	
230011-038	38	0,480	200	3,4	
230011-040	40	0,500	200	3,2	
230011-042	42	0,590	210	3,9	
230011-050	50	0,740	250	3,9	
230011-053	53	0,800	265	3,4	
230011-060	60	0,760	300	3,7	
230011-070	70	1,060	375	3,9	
230011-075	75	1,160	375	3,8	
230011-090	90	1,430	450	4,8	
230011-100	100	1,850	550	4,6	
230011-110	110	1,925	550	6,0	

Vacuum: 0,65 bar

FEATURES: Flexible hose reinforced with rigid helix, light, with great flexibility and good abrasion resistance | APPLICATIONS: Used for light suction and conveying water with electro-pumps and motor-pumps. | TEMPERATURE RANGE: -5/+ 55°C | PRESENTATION: Color: transparent green with white spiral

HELIFLEX LG



Model	Diameter	Weight	Bend Radius	Price
Code	In out	Kg/m	mm	€ / m
230010-020	20 26,2	0,300	100	
230010-025	25 31,4	0,350	125	
230010-030	30 36,4	0,420	150	
230010-032	32 38,6	0,425	160	
230010-035	35 41,6	0,495	160	
230010-040	40 47,2	0,575	200	
230010-042	42 49,4	0,650	210	
230010-050	50 58,0	0,810	250	
230010-053	53 60,6	0,850	265	
230010-060	60 68,4	1,000	300	
230010-075	75 84,4	1,400	375	
230010-090	90 100	1,850	450	

Vacuum: 0,67 bar

FEATURES: Flexible hose reinforced with rigid helix, light, with great flexibility and good abrasion resistance. | APPLICATIONS: Used for light suction and conveying water with electro-pumps and motor-pumps. | TEMPERATURE RANGE: -5/+ 55°C | PRESENTATION: Color: transparent green with white spiral.

HELIFLEX MD



Model	Diameter	Weight	Bend Radius	Price
Code	In out	Kg/m	mm	€ / m
230014-025	25 33	0,500	125	
230014-035	35 44	0,700	175	
230014-042	42 51	0,900	210	
230014-053	53 62,6	1,100	265	
230014-065	65 75	1,500	335	
230014-078	78 90	1,900	390	
230014-105	105 118	2,900	525	
230014-120	120 134	3,400	600	
230014-150	150 166	5,200	750	

Vacuum: 0,70 bar

FEATURES: Flexible reinforced hose with rigid, versatile and abrasion resistant. | APPLICATIONS: Medium suction and sweat and saltwater conveying, chemical solutions and abrasive solids. | TEMPERATURE RANGE: -10/+55°C | PRESENTATION: Color: green

HELIFLEX IND



Model	Diameter	Weight	Bend Radius	Working Pressure	Price
Code	mm	Kg/m	mm	bar	€ / m
302020-053	53	1,40	424	5,0	
302020-060	60	1,60	480	5,0	
302020-080	80	2,25	540	4,0	
302020-090	90	2,60	720	3,0	
302020-100	100	3,20	800	3,0	
302020-110	110	3,70	880	3,0	
302020-120	120	4,00	960	3,0	
302020-125	125	4,15	1000	3,0	
302020-130	130	4,55	1040	2,5	
302020-150	150	6,10	1200	2,5	
302020-200	200	10,30	1600	2,5	
302020-250	250	15,00	2000	2,5	

Vacuum: 0,80 bar

FEATURES: Flexible hose, reinforced with rigid spiral, resistance to collapsing or kinking and abrasion. | APPLICATIONS: Industrial (heavy) suction and conveying fresh and salt water, chemical solutions and abrasive solids. | TEMPERATURE RANGE: -10/+55°C | PRESENTATION: Color: grey.

Platinum TRICOT

(non torsion system)



Model	Inside Dia	Thick-ness	Rupture Pressure	Price
Code	inches mm	mm	bar	€ / m
03PLAT1215	1/2" 13	2,3	20	
03PLAT1220	1/2" 13	2,3	20	
03PLAT1225	1/2" 13	2,3	20	
03PLAT1250	1/2" 13	2,3	20	
03PLAT1515	5/8" 15	2,5	20	
03PLAT1525	5/8" 15	2,5	20	

FEATURES: Combines the braiding tricot with the rubber touch and migration zero of plasticizers. Composition: PVC. | APPLICATIONS: Mainly in the garden, a range of uses in the house and conveying water in general. | COLOR: grey with 3 longitudinal stripes white and golden. Available in lengths of 15, 25 and 50 meters.

Platinum TRICOT



Model	Inside Dia	Thick-ness	Rupture Pressure	Price
Code	inches mm	mm	bar	€ / m
03PLAT1550	5/8" 15	2,5	20	
03PLAT1925	3/4" 19	3,0	20	
03PLAT1950	3/4" 19	3,0	20	
03PLAT2525	1" 25	3,5	20	
03PLAT2550	1" 25	3,5	20	

FEATURES: Combines the braiding tricot with the rubber touch and migration zero of plasticizers. Composition: PVC. | APPLICATIONS: Mainly in the garden, a range of uses in the house and conveying water in general. | COLOR: grey with 3 longitudinal stripes white and golden. Available in lengths of 15, 25 and 50 meters.